

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION

NFPA Rating: Health-1; Flammability-3; Reactivity-0; Special-0	HMIS Rating: Health-1; Flammability-3; Reactivity-0; Personal Protection-B
Manufacturer's Name: AMREP, INC. Address: 990 Industrial Park Drive Marietta, GA 30062	DOT Hazard Classification: ORM-D Identity (trade name as used on label): MISTY DRY DEODORIZERS TRADITIONAL LEMON PEEL (Hand-Held)
Date Prepared: 03/02/00 Prepared By: CH	MSDS Number: 238 LP Revision: 3
Information Calls: (770)422-2071 EMERGENCY RESPONSE NUMBER: 1(800)255-3924	NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
The specific chemical identities of the ingredients of this mixture are considered to be trade secrets and are in accordance with the provisions of section 1910.1200 of Title 29 of the Code of Federal Regulations.	NJ TSRN 238LP				

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A	Specific Gravity (H ₂ O=1): Concentrate Only = < 1
Vapor Pressure: PSIG @ 70°F (Aerosols): 70	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A
Vapor Density (Air = 1): N/E	Evaporation Rate (= 1): N/E
Solubility in Water: Soluble	Water Reactive: No
Appearance and Odor: Clear liquid with fragrance.	

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) NON-FLAMMABLE	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E
FLASH POINT AND METHOD USED (non-aerosols): N/A	SPECIAL FIRE FIGHTING PROCEDURES: Provide shielding for personnel. Wear self-contained breathing apparatus. Cool containers with water fog to prevent rupturing & spewing.	
EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.	Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.	

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY [X] STABLE [] UNSTABLE	HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR
Incompatibility (Mat. to avoid): Alkalis, oxidizing materials, amines.	Conditions to Avoid: Open flame, welding arcs, heat.
Hazardous Decomposition Products: CO, CO ₂ .	

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: ☒ INHALATION ☐ INGESTION ☐ SKIN ABSORPTION ☐ EYE ☐ NOT HAZARDOUS	
ACUTE EFFECTS Vapor concentrations around 1000 ppm may cause slight transient irritation to the upper respiratory tract.	
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.	
Eye Contact: Irritation.	Skin Contact: May cause slight irritation.
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.	
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause mucous membrane irritation, overnight headache, and general weakness.	
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.	

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.
Skin Contact: Wash with soap and water. If irritated, seek medical attention.
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.	Eye Protection: Safety glasses recommended.
Protective Gloves: Latex, if skin easily irritated.	
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.	
Other Protective Clothing & Equipment: None	
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.	

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only