

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)

GENTLE RAIN SHAMPOO

Note: Blank spaces are not permitted. If any item is not applicable, or
information is available, the space must be marked to indicate this.

Section I

Manufacturer's Name

Sween Corporation

Emergency Telephone Number

507-345-6200

Address (Number, Street, City, State, and ZIP Code)

1940 Commerce Drive

Telephone Number for Information

507-345-6200

North Mankato, MN 56003

Date Prepared

January 29, 1991

Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
"THIS PRODUCT IS NOT MANUFACTURED TO CONTAIN A REPORTABLE HAZARDOUS INGREDIENT AS DEFINED IN 29 CFR 1910.1200"				
Water	N.A.	N.A.	N.A.	
Sodium Lauryl Sulfate	N.A.	N.A.	N.A.	
Cocamidopropyl Betaine	N.A.	N.A.	N.A.	
Lauramide DEA	N.A.	N.A.	N.A.	
Glycol Stearate	N.A.	N.A.	N.A.	
Hydrolyzed Animal Protein	N.A.	N.A.	N.A.	
Quaternium-52	N.A.	N.A.	N.A.	
Citric Acid	N.A.	N.A.	N.A.	
Tetrasodium EDTA	N.A.	N.A.	N.A.	
FD & C Yellow #5	N.A.	N.A.	N.A.	(continued)

Section III — Physical/Chemical Characteristics

Bolling Point		Specific Gravity (H ₂ O = 1)	
(above)	212 F		@ 1.03
Vapor Pressure (mm Hg.)	@ 17	Melting Point	N.A.
Vapor Density (AIR = 1)	Similar to water	Evaporation Rate (Butyl Acetate = 1)	Slower
Solubility in Water	Complete		

Appearance and Odor

Viscous Yellow Opaque Liquid with Floral Fragrance

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	N.A.	Flammable Limits	LEL	UEL
		N.A.	N.A.	N.A.

Extinguishing Media

None necessary

Special Fire Fighting Procedures

No special procedures

Unusual Fire and Explosion Hazards

No unusual hazards

(Reproduce locally)

OSHA 174, Sept. 1985