### USE, CARE, & MAINTENANCE OF YOUR ADC PRODUCT





# A Special Thank You...

Thank you for choosing an ADC® emergency product. We're proud of the care and quality that goes into the manufacture of each and every item that bears our name. Only the finest materials are used to assure you of a timeless instrument designed for optimum performance. You'll quickly appreciate the results, for you now own one of the finest emergency tools that money can buy. With proper care and maintenance, your ADC® product is sure to provide you with many years of dependable service. Please read the following instructions and general information which will prove helpful in allowing you to enjoy your ADC® product.

Thank you for your patronage. It is indeed our pleasure to serve you.

Sincerely, American Diagnostic Corp.

©2015 AMERICAN DIAGNOSTIC CORP.

#### Symbol Definitions

The following symbols are associated with your ADC® instrument.

Symbol	Definition
<u> </u>	Important Warning/Caution
[]i	Follow instructions for use.
CATEX	Latex-Free
NHT.	Phthalate Free
Œ	Conforms to EU Standards

Symbol	Definition
REF	Reorder Number
EC REP	Authorized European Representative's Information
•••	Manufacturer's Information

#### Care of your ADC® Nylon holster

Your ADC® Responder nylon holster is made from durable 1000D nylon, lined with cushioning foam. Pocket Organizer is made from 420D nylon.

When soiled, wash by hand in cold water with a mild soap. Never use bleach. Allow holster to air dry. Never iron over hook & loop fasteners-heat from the iron will damage them.

The instrument pockets might be tight initially, but will stretch within a few weeks. Never overload nylon holsters as this may damage the seams or cause the nylon to wear prematurely. We recommend that you do not put sharp-tipped instruments (such as splinter forceps) inside your nylon holster. If, however, you find it necessary to carry a sharp-tipped instrument, place a protective cover (such as a plastic pen cap) over the tips.

## To convert your snap-on belt loop to a permanent belt loop If you do not require the convenience of a snap-on belt loop, and instead prefer the security of a permanent loop you can convert your ADC® nylon holster as follows:

- 1. Obtain a "super glue" or epoxy at your local convenience store.
- 2. Making sure snaps are clean and dry; apply 2 or 3 drops to the male portion of each snap, along the rim and outer edge.
- 3. Snap both snaps closed and allow glue to set according to the directions on the glue package.
- 4. Test that glue snaps hold. If either snap doesn't hold repeat the process.

#### Use of your ADC Knife:

Selected holster sets are equipped with the Puma lockback knife that features a blade forged from 440 surgical stainless steel, tempered to a Rockwell hardness of C57-59.

The PUMA 2002™ is a 4" lockback knife with serrated blade. Thumb activation allows one handed use. It has an integral pocket clip built into the lightweight handle.

To open: Press your thumb against the raised guide on the blade and pivot until it locks.

To close the blade: Depress the metal bar on the back of the knife and push the blade into its chamber until it clicks.

#### Care of your ADC Knife:

Keep the blade clean and dry. Wipe fingerprints and moisture off after each use with a soft cloth or chamois. Keep the locking mechanism free of debris. An occasional drop or two of light oil on working parts will promote smooth operation and long life. Never use knife blade as a chisel, or to cut metal objects.

#### Care of your Medicut™ or MiniMedicut™ Shears

Your Medicut™ #320 and MiniMedicut™ #321 shears, are designed to withstand heavy use. Polypropylene handles, and hardened stainless steel blades assure durability. Never use on thick metal objects, such as a coin- this will damage blade edge. Keep blades clean and dry to prevent corrosion.

To Sterilize: Medicut<sup>™</sup> and MiniMedicut<sup>™</sup> shears may be ETO gas, or steam sterilized to 289.4° F (143° C)

#### Use & Care of your ADC<sup>®</sup> Penlight ADlite™ #356

To activate, depress pocket clip. Release to turn off.

#### Care of your Surgical Instrument(s)

Floor grade surgical instruments are made of 410, 420, or 440 stainless steel. Keep clean and dry. Never use scissors to cut metal or heavy objects.

#### **Limited Warranty**

American Diagnostic Corporation (ADC®) warrants its products against defects in materials and workmanship under normal use and service as follows:

- 1. Warranty service extends to the original retail purchaser only and commences with the date of delivery.
- 2. Holsters, Instruments, and accessories are warranted for one year.
- 3. Medicut<sup>™</sup> and MiniMedicut<sup>™</sup> shears are warranted for 2 years from date of delivery.
- 4. Puma 2002™ is warranted for life.

**What is Covered:** Repair, or replacement of parts, and labor.

**What is not covered:** Transportation charges to and from ADC. Damages caused by abuse, misuse, accident, or negligence. Incidental, special, or consequential damages. Some states do not allow the exclusion or limitation of incidental special or consequential damages, so this limitation may not apply to you.

**To Obtain Warranty Service:** Send item(s) postage paid to ADC, Attn: Repair Dept., 55 Commerce Dr., Hauppauge, NY 11788. Please include your name and address, daytime phone number, proof of purchase, a brief note explaining the problem.

**Implied Warranty:** Any implied warranty shall be limited in duration to the terms of this warranty and in no case beyond the original selling price (except where prohibited by law). This warranty gives you specific legal rights and you may have other rights which vary from state to state.

### To Register Your Product, visit us at www.adctoday.com and follow the links

Comments or Questions Call 1-800-ADC-2670



ADC 55 Commerce Drive Hauppauge, NY 11788

ADC (UK) Ltd.
Unit 6, PO14 1TH
United Kingdom

tel: 631-273-9600 toll free: 1-800-232-2670

fax: 631-273-9659

www.adctoday.com info@adctoday.com

IB p/n 9310-00 rev 7

Printed in the U.S.A.