

PressureGuard® APM²

PressureGuard® APM² with digital control unit



Now made with
LifeSPAN™
bleach-resistant fabric cover
(see page 13 for details)

Therapy Provided

- ✓ Alternating Pressure
- ✓ Lateral Rotation

The APM² has been an industry-leading air therapy solution for more than a decade, based in large part on its documented superiority vs. typical, roll-up treatment surfaces. Newly upgraded cover design and control unit provide even greater immersion, envelopment, shear reduction, treatment flexibility, caregiver ergonomics and user comfort.

QUICK FACTS

Indications:

- Treatment of Stage I – IV pressure ulcers
- Patients that can't/won't reposition frequently
- Can be positioned off pressure ulcer in at least two positions¹
- Prevention for high risk patients

¹ In situations where positioning on the pressure ulcer cannot be avoided (e.g. the individual has multiple ulcers on multiple surfaces), limit the amount of time the individual is positioned on the ulcer. Source: NPAUP/EPUAP Pressure Ulcer Prevention and Treatment, Clinical Practice Guideline, p 66-67

– New, Upgraded Features –

Digital Multi-function Control Unit



Lightweight and quiet, it delivers an unmatched combination of treatment flexibility, ease of use, and dependability.

- Low Pressure indicator light and selectable audible alarm.
- Power Failure indicator light and selectable audible alarm.
- Simple, indexed comfort adjustment.
- Timed (20-minute) "Auto Firm" mode for transfers, ADLs, & CPR.
- "Float" mode provides powered flotation therapy.
- "Alternate" mode changes loading in 10-minute cycle; controlled at mattress for choice of lateral rotation or alternating pressure therapy.




Shear Transfer Zones® Cover Design (US Patent Number 8,438,682)

In addition to the Geo-Matt® segmented top surface, Span-America's exclusive Shear Transfer Zones® provides an additional measure of shearing protection in the form of the silicone-coated, shear-minimizing fabric bands located on the underside of the bi-directional stretch cover.

This Shear Transfer Zones design helps:

- Prevent heels, sacrum, and scapula from "digging into" surface.
- "Glide" user back to original position following HOB elevation.
- Protect against damaging effects of micro shear, macro shear, and rotational (pivot-induced) shear.
- Provide patient stability by transferring shear to more shear-tolerant anchor points.



Item #	Description	Dimensions
5875LR-29	APM ² with digital control unit	75"L x 35"W x 7"H
5880LR-29	APM ² with digital control unit	80"L x 35"W x 7"H
5884LR-29	APM ² with digital control unit	84"L x 35"W x 7"H
5900	Digital control unit only	

Cover: Fluid-proof, coated nylon. Anti-fungal, bacteriostatically treated.

Control Unit:	Weight: 6.3 lbs.	Dimensions: 12" x 7.5" x 5"
	Voltage: 120 AC	Max current: 1.0 Amp
	Frequency: 60 Hertz	UL Listing: Certified to IEC 60601-1-1

Medicare Approved: E0277 (Group II)

Weight limit: 350 lbs **Mattress weight:** approx. 20 lbs.

Warranty: 18 months (all components)

Also available: APM model

Does not include lateral rotation mode. Ships with standard control unit and cover (cover does not include Shear Transfer Zones).

Item #	Description
5175-29	PressureGuard® APM, w/standard control unit, 75"L x 35"W x 7"H
5180-29	PressureGuard® APM, w/standard control unit, 80"L x 35"W x 7"H
5184-29	PressureGuard® APM, w/standard control unit, 84"L x 35"W x 7"H
5500	Standard control unit only

All models are fire barrier version (FBV) as indicated by "-29" suffix, denoting certified conformance to NFPA 101 (Life Safety Code); Cal Tech Bulletin #117; 16 CFR Parts 1632 and 1633; and BFD IX-11.

