Wound Management Smith & Nephew Medical Ltd. 101 Hessle Road Hull HU3 2BN England T 44 (0) 1482 225 181 F 44 (0) 1482 328 326 www.smith-nephew.com



SPECIFICATION Product Safety Data Sheet – ACTICOAT Flex 3 and Flex 7

Approvals

Author Name: David Lloyd

Signature Date/Time: 05 FEB 2019 09:27 UK Global Date/Time: 05 FEB 2019 09:27 UTC

Representation: Author Signature

Signature Reason: Document Management: Status Change

Signatory Name: Vivienne Pooleman

Signature Date/Time: 21 MAR 2019 11:02 UTC Global Date/Time: 21 MAR 2019 11:02 UTC Representation: Engineering Signature

Signature Reason: Document Management: Status Change

SPECIFICATION

Product Safety Data Sheet - ACTICOAT Flex 3 and Flex 7

SPECIFICATION

Product Safety Data Sheet

1a) PRODUCT NAME(S): ACTICOAT Flex 3

ACTICOAT Flex 7

1b) INTENDED USE(S):

For external use as an antimicrobial barrier layer over partial and full thickness wounds such as pressure ulcers, venous leg ulcers, burns and donor recipient graft sites.

1c) Details of Supplier of the Product Safety Data Sheet:

Compliance & Regulatory Department Smith & Nephew Healthcare Healthcare House 101 Hessle Road Hull

HU3 2BN

Telephone: 01482 222200 Fax: 01482 222211

Email Address: Advice.Healthcare@smith-nephew.com

2. HAZARD INFORMATION:

Avoid contact with electrodes or conductive gels during electronic measurements e.g. EEG or ECG. Do not use on patients undergoing MRI (Magnetic Resonance Imaging) examination.

Health effects: Do not use on patients with a known sensitivity to silver. May cause transient discolouration of the surrounding skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS:

Both products are composed of knitted polyester (100%) coated with nanocrystalline silver. Flex 3 contains less silver than Flex 7.

4. FIRST AID:	
a) Inhalation	Not applicable
b) Contact with skin	Skin irritation may result as an allergic reaction to silver content of the dressing. Obtain medical attention if irritation persists or develops.
c) Contact with eyes	Corneal irritation may occur as a result of mechanical abrasion. In the event of eye irritation – flush eyes with flowing water.
d) Ingestion	May cause a choking hazard or internal blockage. Obtain medical attention.

5. FIRE AND EMERGENCY MEASURES:

The product is a combustible solid which gives off toxic fumes, mainly carbon monoxide and carbon dioxide when ignited. If involved in a fire, treat as a flammable solid. Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES:

Not Applicable

7. HANDLING AND STORAGE PRECAUTIONS:

Handling – no special procedures required. If used, handle as medical waste. Storage – avoid exposure to temperatures above 50°C. Protect from light.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

Not Applicable

9. PHYSICAL AND CHEMICAL PROPERTIES:

Colour – grey (variation may occur).

Odour - none associated with the dressing.

10. STABILITY AND REACTIVITY:

ACTICOAT Flex 3 and 7 are not compatible with oil based products such as petrolatum.

11. TOXICOLOGICAL INFORMATION:: See information in Hazard Information			
12. ECOLOGICAL INFORMATION: Not Applicable			
13. DISPOSAL CONSIDERATIONS: Material should be considered as medical waste after use. Dispose of according to local guidelines			
14. TRANSPORT INFORMATION: Not Applicable			
15. REGULATORY INFORMATION: Not Applicable			
16. ADDITIONAL INFORMATION: Not Applicable			
18a) REFERENCE NUMBER	2002497		
18b) DATE OF ISSUE	February 2019		

This information is provided in accordance with the requirements of the UK Health and Safety at Work Act 1974, and specifically in order to assist users of the product to make their 'assessment of health risks' as required by the UK Control of Substances Hazardous to Health Regulation 2002 (COSHH assessments). Provision of this information does not preclude users from seeking advice from other sources as indicated in the COSHH guides. The information is intended to cover potential hazards at the place of work and does not detail medical uses, indications, contra-indications and precautions for the treatment of patient.

REASON FOR CHANGE

Document Version	Section/Paragraph Changed	Change Made	Date
1	ALL	First Issue	28/08/09
2	Product codes	Added in additional approved product codes to listing.	08/06/2010
3	N/A	Re-issue following scheduled review. No change to information. Format change to latest template.	17/06/13
4	All	Re-issue following scheduled review. Information transferred into current template. No change to content.	03/02/16
5	N/A	Re-issue following scheduled review.	5 th Feb 2019

RE-VERIFICATION OF DOCUMENT SUITABILITY

The normal expiry date/time for a printed <u>non-controlled</u> document is 06:00 on the day after the date the document was printed. If such a document is required for more than one day, rather than print a new copy each day, the existing printout can be manually compared to the electronic copy. If it is the same version, you may sign and date the following agreement for each additional day:

"I have compared this paper copy to the original electronic copy on the date shown below and certify that both are the same version number"

Print Name	Signature	Date

Plant Number(s): None	
Product Code(s): 66800395, 66800396, 66800397, 66800398, 66800399, 66800400, 66800401, 66800403 66800405, 66800407, 66800408, 66800409, 66800419, 66800420, 66800427, 66800432 66800435, 66800545	
*** END OF DOCUMENT ***	
*** END OF DOCUMENT ***	