

Short-term Monitoring

BlueSensor M



Size: 34 mm diameter

BlueSensor Q



Size: 40 mm diameter

Features and Benefits

- Highly conductive wet gel - ensures reliable traces
- Superior adhesion - prevents false alarms
- Occlusive backing material - is resistant to fluids
- Unique offset connector - prevents artifact from disrupting the readouts
- High-quality Ag/AgCl sensor - ensures excellent trace quality
- Fast and easy to use - optimizing workflow and cost efficiency



Product	Pack	Box	Case
M-00-A/50	50	1000	2000
M-00-F/50	50	1000	2000
M-00-S/50	50	1000	2000
Q-00-S/25	25	500	1000

BlueSensor Electrodes for ECG - Single-use

Product Name	Application	Gel type	Backing material	Size (mm)	Shape	Shelf life (months)	Radiolucent
BlueSensor M 	Short-Term	Wet	Polymer	Diameter: 34	Round w/ offset	15	No
Reference Numbers	Connector type	Pcs/liner	Units/pack	Units/box	Units/case		
M-00-A/50	4 mm	1	50	1000	2000		
M-00-F/50	3 mm	1	50	1000	2000		
M-00-S/50	Snap	1	50	1000	2000		

Product Name	Application	Gel type	Backing material	Size (mm)	Shape	Shelf life (months)	Radiolucent
BlueSensor N 	Pediatric	Wet	Foam	30 x 22 (wired), 44.8 x 22 (non wired)	Oval	24 (non wired), 12 (wired)	No
Reference Numbers	Connector type	Lead wire length (cm)	Color of wires	Pcs/liner	Units/pack	Units/box	Units/case
N-00-A/25	4 mm	None	None	1	25	1000	2000
N-00-F/25	3 mm	None	None	1	25	1000	2000
N-00-S/25	Snap	None	None	1	25	1000	2000
N-10-A/25	4 mm	10	○	1	25	1000	2000
N-10-F/25	3 mm	10	○	1	25	1000	2000
N-50-F/25	3 mm	50	○	1	25	500	1000
N-50-K/25	3 mm	50	○	1	25	500	1000

Product Name	Application	Gel type	Backing material	Size (mm)	Shape	Shelf life (months)	Radiolucent
BlueSensor NEO X 	Neonatal	Solid	Polyurethane	25 x 20	4-leaf clover	24	Yes
Reference Numbers	Connector type	Lead wire length (cm)	Color of wires	Pcs/liner	Units/pack	Units/box	Units/case
NEOX-60-K/US/3	1.5 mm	60	●●○	3	3	120	960

Product Name	Application	Gel type	Backing material	Size (mm)	Shape	Shelf life (months)	Radiolucent
BlueSensor NF 	Neonatal	Solid	Cloth	30 x 22 (wired), 44.3 x 22 (non wired)	Oval	24	No
Reference Numbers	Connector type	Lead wire length (cm)	Color of wires	Pcs/liner	Units/pack	Units/box	Units/case
NF-00-S/12	Snap	None	None	3	12	1200	2400
NF-10-A/12	4 mm	10	○	3	12	600	1200
NF-50-A/12	4 mm	50	○	3	12	600	1200
NF-50-K/US/3	1.5 mm	50	●●○	3	3	600	1200
NF-50-K/W/12	1.5 mm	50	○ (wound)	3	12	600	1200

Connectors and Fittings:



A = 4 mm
Connector



F = 3 mm
connector



J = 2 mm
connector



K = 1.5 mm
connector