

ASSURE® DOSE CONTROL SOLUTIONS



**Assure® Dose
Control Solution
Normal**



**Assure® Dose
Control Solution
High**

ORDERING DETAILS

ARKRAY Product Code#	NDC#
Assure® Dose Control Solution (Normal and High) 500006	08317-5000-06

ASSURE® PLATINUM METER SPECIFICATIONS

For additional information refer to the Assure® Platinum User Manual.

Product Specifications	
Test strips	Assure Platinum Test Strips
Result range	20–600 mg/dL
Calibration	Plasma referenced
Sample size	Minimum 0.5 µL
Blood source	Capillary whole blood
Test time	7 seconds
Assay method	Biosensor, Glucose oxidase (<i>Aspergillus niger</i> sourced) and Hexaammineruthenium (III) chloride
Power source	Two 1.5V alkaline AAA batteries
Battery life	More than 5,000 tests at 4 tests per day
Display type	Liquid Crystal Display (LCD)
Memory	500 results with time and date stamp
Average	7-, 14-, 30-, and 90-day averaging
Automatic shut off	2 minutes after last user action
Size	4.5" x 2.5" x 1.2"
Weight	2.8 oz. (without batteries)

Operating Ranges	
Temperature	50°F–104°F (10°C–40°C)
Relative humidity	20%–80%
Hematocrit	30%–55%
Altitude	10,000 ft. (3,048 meters)
Unit of measurement	mg/dL